





ISO 9001:2008

TECHNICAL DATASHEET

Packing

25 kg to 125 kg

البيانات الفنية للمنتاجات

Brand Name	KB 116 N				اســـم المنتج
Product	Adhesive for tube winding (cones) (کونات) اسیر الکرتون (کونات)			غراء خاص بموا	المنتج
Lab. Code	ADH – 2 – 21				کود معملي
Applications	on automatic m 50°C. Especiall winding adhesive tube (cones) co cones, toilet partubes etc.	liquid adhesive suitable for use tic machines as is or heated at ecially developed as a tube thesive to be used in all paper es) constructions such as yarn et paper tubes, aluminum foil litization in a fast drying time and quick the strengthens paper tubes and s deformation.		الاســـّـخـــدامـات	
Properties	Base	Modified natural carbohydrate polymer / organic additives	محورات نشوية كيماوية/حرارية مع مواد مساعدة عضوية	الأسياس	المــــــــــــــــــــــــــــــــــــ
	Color	Whitish	مائل للابيض	الـــــون	
	Safety	Neither flammable nor toxic – Solvent free.	غير قابل للاشتعال أو سام ـ لا يحتوي على مواد طيارة .	الأمــــان	
Technical Info.	Before drying of the film قبل جفاف الطبقة اللصق				
	Solid Content	18 ± 2 %		المسادة	معلومات -
	Viscosity	5000 - 6000 cps /20°C)		الــــــزوجـــة	
	pН	5 – 7		الرقــم	
	Setting time	3 – 4 minutes for 0.25 mm		زمن	
	Thinning	Up to 30%		التخفيف	
	After drying of the film بعد جفاف الطبقة اللصق				
	Appearance	Whitish	مائل للابيض	المظهر	
	Elasticity	Stiff not elastic	صلب غير مرن	الليونــــة	
Shelf life & Storage	stored in its	ear from production date if original tightly closed lry place away from direct essive heat.	ن تاريخ الإنتاج المدون، شرط حفظها بعيداً عن حرارة وأشعة بمكان جيد التهوية.	سلامة العبوة، و.	الصلاحية والتخــزيــن

Disclaimer: The information & data contained herein are given in good faith but without warranty. We recommend that before using our products, the customer should make his/her own tests to determine the suitability of the products for his/her own purpose under his/her operating conditions. As the circumstances under which our products are stored, handled and used are beyond our control, we cannot assume any responsibility for their use by the customers.

من 25 الي 125 كجم

التعىئية