





ISO 9001:2008

البيانات الفنية للمنتاحات

TECHNICAL DATASHEET

Brand Name	KF 10	اســـم المنتج	
Product	Lamination Adhesive : varnished duplex paper with treated cellophane paper	غراء لامينيشن: ورق الديوبلكس مع ورق السيلوفان المعالج	المنتج
Lab. Code	ADH – 2 – 11		كود معملي

Ready for use high quality adhesive manufactured with the finest raw materials. Especially recommended for lamination of glossy or mat varnished duplex paper with treated cellophane paper. When spread on surface to be laminated, it gives an even film without any defects which show on excellent wetting properties. Base Plasticized synthetic resin emulsion Color Milky white emulsion Safety Neither filammable nor toxic – Solvent free Neither filammable nor toxic – Solvent free Solid Content 50 ± 2 % University 40.000 ± 5000 cps /20°C) Ph 5 - 5.5 Dh Gatting time Can be diluted from 10 to 20% with clean water year. After drying of the film Appearance Transparent Elasticity Very elastic Shelf life & Storage Packing 25 kg to 125 kg Ready for use high qualestive manufactured with the finest raw materials. Expectation and related to faminate and in a fixed place and pla						
Properties Color Milky white emulsion الله الله الله الله الله الله الله ال	Applications	manufactured with the finest raw materials. Especially recommended for lamination of glossy or mat varnished duplex paper with treated cellophane paper. When spread on surface to be laminated, it gives an even film without any defects which show on excellent wetting		الخامات الأولية. يوصى به خصيصاً لعمل المينيشن لورق الديوبلكس المورنش سواء المط أو اللامع، مع ورق السيلوفان المعالج. عند عمل طبقة من هذه المادة على الأسطح المراد عمل لامينيشن لها، فإنه يعطى طبقة متجانسة دون أي شوائب أو عيوب، مما يؤكد أن		الاستخدامات
Neither flammable nor toxic – Solvent free - مال الله الله الله الله الله الله الله	Properties	Base			الأسياس	
Before drying of the film Solid Content 50 ± 2 % 50 ± 2 % Viscosity 40.000 ± 5000 cps /20°C) 40.000 ± 5000 cps /20°C PH 5-5.5 7-5.5 Setting time Can be diluted from 10 to 20% with clean water 40.000 ± 5000 cps /20°C Setting time Can be diluted from 10 to 20% with clean water 40.000 ± 5000 cps /20°C Setting time Can be diluted from 10 to 20% with clean water 40.000 ± 5000 cps /20°C Setting time Can be diluted from 10 to 20% with clean water 40.000 ± 600		Color	Milky white emulsion	مستحلب أبيض	الْــــــون	السواصفات
Solid Content 50 ± 2 % المادوجة Viscosity 40.000 ± 5000 cps /20°C) المادوجة PH 5-5.5 الموقع PH 5-5.5 الموقع Ph Setting time Can be diluted from 10 to 20% with clean water الجفاف المعنى تخفيف بنسبة تصل من 10 الي 20% بالماء النقي After drying of the film Appearance Transparent Italia Transparent Italia Italia		Safety		, -	الأمــــان	
Technical Info. PH 5-5.5 الرقام Setting time Can be diluted from 10 to 20% with clean water of the film المحكن تخفيف بنسبة تصل من 10 الي 20% بالماء النقي After drying of the film After drying of the film Appearance Transparent Elasticity Very elastic Valid for one year from production date if stored in its original tightly closed container in a dry place away from direct sunlight and excessive heat. Transparent but on the place and pl	1 0 0 1 1 1 1 1 0 1 1 1	Before drying				
Technical Info. pH 5-5.5 رمال الرقام Setting time Can be diluted from 10 to 20% with clean water pain in the part of the film of the film part of the film		Solid Content	50 ± 2 %		المسادة	
Technical Info. Setting time Can be diluted from 10 to 20% with clean water (بالماء النقي المفاف العلق المفاف العلق المفاف العلق		Viscosity	40.000 ± 5000 cps /20°C)		الــــــزوجـــة	
Info. Can be diluted from 10 to 20% with clean water (رمين) رمين		рН	5 – 5.5		الرقــم	معلومات
Appearance Transparent والمنط الماليونة الماليونة كالماليونة Shelf life & Storage Appearance Transparent الماليونة عالم من تاريخ الإنتاج المدون، شرط الماليونة العبوة، وحفظها بعيداً عن حرارة وأشعة والتخزين الشمس المباشرة بمكان جيد التهوية.		Setting time			· ·	فنيــة
Elasticity Very elastic الليونة عالي الليونة الإنتاج المدون، شرط Valid for one year from production date if stored in its original tightly closed container in a dry place away from direct sunlight and excessive heat. Shelf life & Storage Valid for one year from production date if stored in its original tightly closed container in a dry place away from direct sunlight and excessive heat.		After drying of the film				
Shelf life & Storage Valid for one year from production date if stored in its original tightly closed container in a dry place away from direct sunlight and excessive heat. Valid for one year from production date if stored in its original tightly closed container in a dry place away from direct sunlight and excessive heat.		Appearance	Transparent		, ,	
Shelf life & stored in its original tightly closed container in a dry place away from direct sunlight and excessive heat. stored in its original tightly closed container in a dry place away from direct sunlight and excessive heat.		,	•	عالي الليونة	الليونــــة	
<u> </u>		stored in its original tightly closed container in a dry place away from direct		سلامة العبوة، وحفظها بعيداً عن حرارة وأشعة		-
	Packing			من 25 الي 125 كجم		التعبئة

Disclaimer: The information & data contained herein are given in good faith but without warranty. We recommend that before using our products, the customer should make his/her own tests to determine the suitability of the products for his/her own purpose under his/her operating conditions. As the circumstances under which our products are stored, handled and used are beyond our control, we cannot assume any responsibility for their use by the customers.